



BALLISTI SEAL - BASIC



11720 Main St, Suite 120
Fredericksburg, VA 22408
540-940-6698
admin@supplyndesign.com
www.supplyndesign.com

TECHNICAL DATA SHEET

Issue Date: 12-OCOTBER-22

Revision Date: 12-OCTOBER-22

Alt. Identifier: N/A

DESCRIPTION: BallistiX BallistiSeal - Basic

BallistiSeal Basic, a water-based acrylic coating, enhances the color of any stained floor while remaining virtually odorless. It provides the durability of a typical solvent-based sealer without hazards. BallistiSeal Basic is used as a sealer and a beautifier for any interior areas where flammable solvent-based sealers are too hazardous to use.

Available in 5 gallon buckets.

PRODUCT HIGHLIGHTS

- Does not emit toxic or flammable fumes and can be used wherever there is normal ventilation.
- Not combustible or flammable. There is essentially no risk of fire with this product.
- Provides a non-toxic, colorless and odorless seal once dry and fully cured.
- This tough coating is non-slip and non-blushing when wet and is both water and scuff resistant.
- Ultra-low VOC coating with no aromatic or chlorinated solvents.
- Meets all California VOC standards.
- With regular care, BallistiSeal Basic will never wear or need re-coating.

PRIMARY USES

Stained or Dyed Concrete Floors

Walls

Countertops

PRODUCT SPECS

Type: Stable water-based dispersed coating

Toxicity: Low - Harmful if swallowed

VOC's: Less than 100gm per L

Flammability: Non-flammable

Composition: Special proprietary resins in a solvent

Solids: 31% (+/-)

Color: Dry coat is colorless

Odor: Mild

Coverage: 800-1000 sq.ft. *Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided. FOR MORE INFORMATION, PLEASE SEE SDS.



BALLISTISeal - BASIC



11720 Main St, Suite 120
Fredericksburg, VA 22408
540-940-6698
admin@supplyndesign.com
www.supplyndesign.com

TECHNICAL DATA SHEET

DIRECTIONS FOR USE

It is imperative that your surface is clean and free of oil, dirt, and chemical residue before applying this product. Acid-stained floors must be rinsed thoroughly to be free of any residues and dry before sealing.

Once your floor is thoroughly cleaned and completely dry, apply BallistiSeal Basic using a roller. Apply three thin coats. Coverage for each coat should be roughly 800 – 1000 sq. ft. per gallon.

Allow each application to dry for one hour before applying the next coat. Allow the product to dry for 24 hours before permitting any traffic.

Do not apply too heavily. Make sure the concrete is cured and totally dry before applying. Do not allow the product to puddle. Any lines, high areas, or marks created by the roller need to be rolled back out to level out while still wet.

CLEANING

Wash brushes and equipment with warm water and soap. Rinse clean.

SAFETY

Do not use this product until all safety precautions have been read and understood. Wash your skin thoroughly after handling and do not eat, drink or smoke while using this product. Remember to wear protective gloves/protective clothing/eye protection/face protection. Dispose of contents/containers according to local, state, and federal regulations.

FIRST-AID

EYES: Flush with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INHALATION: Remove to fresh air immediately. If breathing difficulties continue, Get Medical Help.

INGESTION: Do not induce vomiting. Rinse mouth with water, and drink two glasses of water. Get Immediate Medical Help.

SKIN: Wash with soap and water. Remove contaminated clothing and launder before reuse.

IN CASE OF FIRE: This product is not flammable.

FOR PROFESSIONAL USE ONLY

FOR EMERGENCY HELP
24 Hours a Day contact: INFOTRAC at 1-800-535-5053